

This listing of claims will replace all prior versions, and listings, of claims in the application.

### LISTING OF CLAIMS

1-27. (Canceled)

5

28. (Previously presented) A method for encoding and decoding a digitized image having picture elements, said method comprising the steps of:

10           grouping all except at least one picture elements of said digitized image  
              into a number of image segments based on a mathematically  
              defined region of said digitized image derived solely from said  
              digitized image itself, said at least one ungrouped picture element  
              being from at least one area of said image located between image  
              segments;

15           encoding said image in said first arrangement by only encoding said  
              picture elements being grouped into an image segment;

              transmitting said encoded image segments from said first arrangement to  
              a second arrangement;

              decoding said transmitted image segments in said second arrangement;

20           inserting new picture elements corresponding to said non-encoded picture  
              elements of said encoded image in said second arrangement in an  
              area between said decoded image segments;

              interpolating said area between said image segments in said second  
              arrangement; and

25           allocating encoding information resulting from said interpolating to said  
              new picture elements.

29. (Currently amended) The method according to claim 28 ~~27~~, further comprising the step of:

prior to encoding said grouped picture elements, filtering said image to be encoded.

5

30. (Previously presented) The method according to claim 28, wherein said interpolation is performed by low-pass filtering.

31. (Previously presented) The method according to claim 28, further comprising  
10 the step of:

prior to encoding said grouped picture elements, filtering said image to be encoded; and

wherein said interpolation is performed by low-pass filtering.

15 32. (Previously presented) The method according to claim 30, wherein said low-pass filtering is performed essentially at edges of said image segments.

33. (Previously presented) The method according to claim 30, wherein said filtering is performed after said decoding.

20

34. (Previously presented) The method according to claim 33, wherein said filtering is performed essentially at edges of said image segments.

35. (Currently amended) The method according to claim 28 ~~27~~, wherein said  
25 image segments are image blocks.

36. (Previously presented) The method according to claim 35, wherein at least respectively one picture element is not grouped into any image block between said image blocks.

5 37. (Previously presented) The method according to claim 28, wherein said interpolating is performed by a number of filters.

38. (Previously presented) The method according to claim 37, wherein said filters have characteristics dependent on an image quality of an image block; and  
10 wherein a strength characteristic of a filter increases with a reduction of said image quality of said image block.

39. (Previously presented) The method according to claim 37, wherein said filters have characteristics dependent on a motion vector of an image block; and  
15 wherein a strength characteristic of a filter increases with a size of a motion vector being allocated to a respective image block.

40. (Currently amended) The method according to claim 28 ~~27~~, wherein said encoding is according to the H.263 standard.

20

41. (Previously presented) The method according to claim 28, wherein said encoding is according to the H.263 standard; and wherein said encoded image is transmitted from said first arrangement to said second arrangement by employing a capability table according to the H.245 standard.

25

42. (Currently amended) The method according to claim 28 ~~27~~, further comprising the step of:

implementing a motion compensation upon said digitized image.

43. (Cancelled).

5 44. (Previously presented) An arrangement for encoding and decoding a digitized image having picture elements, said arrangement comprising:

a first arrangement having a first processor unit comprising a processor and a memory including a program comprising the steps of:

10 grouping all except at least one picture elements of said digitized image into a number of image segments based on a mathematically defined region of said digitized image derived solely from said digitized image itself, said at least one ungrouped picture element being from at least one area of said image located between image segments; and

15 encoding said image by only encoding said picture elements being grouped into an image segment;

a transmitter for transmitting said encoded image from said first arrangement to a second arrangement;

20 a second arrangement having a second processor unit comprising a processor and a memory including a program comprising the steps of:

decoding said transmitted image segments;

25 inserting new picture elements corresponding to said non-encoded picture elements of said encoded image in said second arrangement in an area between said decoded image segments;

interpolating said area between said image segments in said second arrangement; and

allocating encoding information resulting from said interpolating to said  
new picture elements.

45. (Previously presented) The arrangement according to claim 44, wherein said  
5 - second processor unit is programmed to interpolate by low-pass filtering.

46. (Currently Amended) The arrangement according to claim ~~44~~ 43, wherein  
said first processor unit is programmed to realize said image segments as image  
blocks, and wherein at least respectively one picture element is not grouped  
10 into any image block between said image blocks.

47. (Previously presented) The arrangement according to claim 44, wherein  
said second processor unit is programmed to perform said interpolating by a  
number of filters.

15

48. (Previously presented) The arrangement according to claim 47, wherein  
said wherein said filters have characteristics dependent on an image quality of  
an image block; and wherein a strength characteristic of a filter increases with a  
reduction of said image quality of said image block.

20

49. (Previously presented) The arrangement according to claim 47, wherein said  
filters have characteristics dependent on a motion vector of an image block; and  
wherein a strength characteristic of a filter increases with a size of a motion  
vector being allocated to a respective image block.

25

50. (Currently amended) The arrangement according to claim ~~44~~ 43, wherein  
said first processor unit is programmed to encode according to the H.263  
standard.

51. (Previously presented) The arrangement according to claim 45, wherein said first processor unit is programmed to encode according to the H.263 standard; and wherein said encoded image is transmitted from said first arrangement to said second arrangement by employing a capability table according to the H.245 standard.

52. (Currently amended) The arrangement according to claim 44 ~~43~~, wherein said first processor unit is programmed to implement a motion compensation upon said digitalized image.